



Specifications		Unit	NCL-30
Collet Chuck	Max. Turning Diameter	mm	Φ 30
Jaw Chuck		mm	Φ 125
Max. Turning Length		mm	210
Max. Bar Capacity		mm	30
Main Spindle Bore		mm	42
Spindle Nose			A2-5
Spindle Speed		r.p.m.	40~6000
Spindle Motor Power		HP	5
Stroke of X /Z		mm	380 /220
Rapid Traverse		M/min	15
X/Z Axis Servo Motor		Kw	1
X/Z Ballscrew Diameter		mm	25
X/Z Linear Guide		mm	30
Servo Turret	Number of Tools	PCS.	8
	Turning of Diameter	mm	16
	Boring Tool Diameter	mm	20
Sub-Gantry	Number of Tools	PCS.	2
	Turning of Diameter	mm	16
	Boring Tool Diameter	mm	20
Positioning of Axis		mm	0.005
Repeatability of Axis		mm	0.003
Coolant Tank Capacity		L	150
Dimension (M)		mm	2000x1500x1800
Machine Weight		Kgs	3000

Accessories with Machine:-

- AVR
- UPS for Controller
- Heat Exchanger
- 5" 3-Jaw Chuck
- Collet Chuck
- Chip Conveyor
- Toolholders for Demo
- Vernier Caliper
- 02 Years Warrantee on Controller



Dynamic Tooling Services

Islamabad Office

Ph: 051-2806197 / 2870601

Cell: 0321-2442117

Email: proc@dts.com.pk

Showroom & Lahore Office

Mr. Nadeem Iqbal

Cell: 0321-4480051

Email: lahore@dts.com.pk

Karachi Office

Mr. Tahir Nazir

Cell: 0321-23080383

Email: karachi@dts.com.pk